



DET NORSKE VERITAS

TYPE APPROVAL CERTIFICATE

CERTIFICATE NO. P-14256

This is to certify that the
Pipe Couplings, Bite and Compression Type

with type designation(s)

ES-V, W-V, GS-V, T-V, G-V, WS-V, K-V, WE-V, GE-V, TE-V, LE-V, TR-V, EG-V, EW-V, ET-V, EL-V, MA-V, MA-EV, MA-VD, EW-VD, ET-VD, EL-VD, EG-VD, KOR-V, RED-V, GAS-V, GAI-V, GR-V, ETH-V and EWH-V

Manufactured by

Volz Gruppe GmbH
DEILINGEN, Germany

is found to comply with


Det Norske Veritas' Standards for Certification 2.9 No. 5-792.20
Det Norske Veritas' Rules for Classification of Ships and Mobile Offshore Units

Application

May be used for: Hydraulic- and lubrication oil, fuel oil (not high-pressure fuel injection), compressed air, oxygen (see cert.), steam and condensate, fresh- and sea water

Temperature range: (See Cert.)
Max. working press.: 100 to 800 bar (See Cert.)
Sizes: Tube O.D. 4 to 42 mm

Høvik, 2012-12-06
for Det Norske Veritas AS


Giorgio Saia
Acting Head of Section



DNV local office:
DNV Essen

This Certificate is valid until
2016-06-30


Mohsen Mohebbi
Surveyor

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

If any person suffers loss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 2 million. In this provision "Det Norske Veritas" shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.



Certificate No.: P-14256
 File No.: 792.21
 Job Id.: 262.1-005646-3

Product description

Cutting ring pipe couplings acc. to DIN 2353.

Materials:

Couplings: Stainless steel, X6CrNiMoTi17-12-2, No.1.4571 DIN EN 10088-3
 Sealing rings: FPM or PTFE

Coupling types:

ESV	Welding bulkhead	MA-V	Manometer coupling
W-V	Equal elbow	MA-EV	Adjustable manometer coupling
GS-V	Threaded bulkhead	MA-VD	Adjustable manometer coupling
T-V	Equal tee	EW-VD	Adjustable W-coupling
G-V	Straight coupling	ET-VD	Adjustable T-coupling
WS-V	Bulkhead elbow	EL-VD	Adjustable L-coupling
K-V	Equal cross	EG-VD	Standpipe adaptor
WE-V	Male stud elbow	KOR-V	Reducing standpipe
GE-V	Male stud straight	RED-V	Reducing standpipe
TE-V	Male stud branch tee	GAS-V	Straight welding coupling
LE-V	Male stud barrel tee	GAI-V	Straight female adaptor
TR-V	Male stud branch tee	GR-V	Straight reducing
EG-V	Standpipe adaptor	ETH-V	Adjustable T-swivel
EW-V	Adjustable barrel tee	EWV-V	Adjustable W-swivel
ET-V	Adjustable barrel tee		
EL-V	Adjustable barrel tee		

Adaptors available with conical or cylindrical thread.

Application/Limitation

Normal working pressures defined at 20°C:

Product line	Tube O.D. mm	Pressure Bar
LL	4 - 8	100
L	6 - 10	500
L	12 - 18	400
L	22 - 42	250
S	6 - 10	800
S	12 - 16	630
S	20 - 38	420

At elevated temperatures, the maximum pressures are to be reduced according to following:

Temperature, °C:	50	100	200	300	400
Reduction, %:	4.5	11	20	29	33

Temperature range depending on sealing ring materials:

FPM (Viton):	-25 to 200°C
PTFE (Teflon):	-60 to 200°C

Coupling series L and S may be used for gases having an oxygen content exceeding 21% at working pressure 250 bar respectively 360 bar.

Couplings used for low temperature gas may only be used for accessory lines and instrumentation lines with external diameters of 25 mm and less. DNV Rules Pt.5, Ch.5, Sec.6, C509

Threaded bulkhead couplings type GS-V and WS-V may not be used on watertight bulkheads.

Couplings with non-metallic components are not to be used for fire safe applications.

Mollob



Certificate No.: P-14256
File No.: 792.21
Job Id.: 262.1-005646-3

The approval is only valid when the couplings are assembled with tubing of correct temper and tolerances as recommended by the manufacturer.

These couplings are not to be used on tubes in cold fabricated (hard temper) conditions.

The wall thickness and material of the tubes to be in accordance with the current Rules of Det Norske Veritas.

No product certificate will be required.

Type Approval documentation

Reference documents:

- Manufacturer's catalogue
- Test witnessed by DNV, 1995-03-02
- DNV test report no. 95-1017, Oxygen shock test, 1995-02-23
- MPA NRW Prüfzeugnis Nr. 12 0016 0 95, 1994-12-19
- Test witnessed by DNV 2004-04-02, Pruf-Nr 04/020
- Test witnessed by DNV 2004-04-30, Pruf- Nr 04/020-1
- Retention Survey Report Date: 28,04,2008
- SZMF Test Report D 048/2008 Date: 12,03,2008
- Flextest test reports dated 2008-09-24
- Salzgitter Mannesmann Forschung test reports
- Survey report ESN-09-32242 including test reports
- Survey report dated 2012-07-18 including test reports

Tests carried out

Leakage, Burst Pressure, Vacuum test, Pull-Out, Repeated assembly test, Vibration, Pressure Pulsation Test, Oxygen shock test,

Marking of product

For traceability to this type approval, each coupling is at least to be marked with:

- Manufacturer's trade mark
- Type designation
- Size

Certificate Retention Survey

For retention of the Type Approval, a DNV Surveyor shall perform a survey - before the expiry date of this certificate - to verify that the conditions for the type approval are complied with. The Surveyor shall perform the following tasks on samples selected at random from stock or from the running production:

- Verify that the dimensions of the couplings comply with Type Approved documentation.
- Verify that the material composition complies with Type Approved documentation.
- Witness burst testing.

The burst testing may be omitted at the Surveyor's discretion.

END OF CERTIFICATE